

EAGLE INKJET MEDIA



SOLVENT BACKLIT 200 MATTE

Details

- Translucent polyester backlit film designed for Excellent image quality graphic art applications.
- Semi-matte coating with less glare and high quality image density.
- Easy to install due to the rigid and flat substrate.
- Available in widths up to 87".
- Flame Class: VTM-2 (Polyester Film)

Specifications

Length (ft)	100	Width (inch)	36"/54"/60"/72"/87"
Weight (gsm)	275	Coating	Resin
Caliper (mil)	8.2	Base Material	PET
Inner Core (inch)	3	Printer	ESLUV
Surface	Matte		

KEY FEATURES

- Universal printability for most printers
- High Contrast & High Image Density
- Translucent PET Film
- Matte surface
- Up to 87"

Application & Guideline

- Lightbox Graphic, Backlit Trade Show Display, Department Store Display, Luminous Advertising Surface, Bus Shelter & Metro Illuminated Signage
- Outdoor durability 1 year without overlaminate, 2 year with overlaminate

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional.
- Storage : Recommended to store in closed original packaging in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.
(Humidity 35~65% RH)
- Shelf Life : One year stored in original packaging at recommended temperature.
(Coating warranty guaranteed for 6 months from date of purchase)

How to buy :



WALKER SUPPLY COMPANY

Graphics Equipment and Supplies

800-775-9528 • www.walkersupply.com

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.
All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.