



Adhesive Backed 3.5 mil Gloss Clear Vinyl Removable Adhesive for Solvent & UV Printers

- Can be used for interior and exterior signage
- Uses include advertising, stickers, decals, point of purchase displays or window graphics
- For window graphics that are wet applied
- Compatible with OEM Solvent and UV Curable Inks

Construction

Product Number:	SOL/35CLEARCAL/xxR
Adhesive:	Clear Removable Acrylic
Film:	3.5 mil Vinyl
Liner:	90 lb Polycoated two sides
Finish:	Gloss Clear
Gloss Level:	80 (avg.) @ 60°

Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Printing:	Outdoor - 3 years unprinted				
Minimum Application Temperature:	+50° F (Minimum for Substrate)				
Service Temperature Range:	-40° F to + 180° F				
Chemical Resistance:	Resistant to alkalis, mild acids, most petroleum based oil, grease and aliphatic solvents and salts.				
Typical Adhesion Values:	180° Peel Test <table><tr><td><u>Substrate</u></td><td><u>24 hrs.</u></td></tr><tr><td>Stainless Steel</td><td>1.8 lb/in</td></tr></table>	<u>Substrate</u>	<u>24 hrs.</u>	Stainless Steel	1.8 lb/in
<u>Substrate</u>	<u>24 hrs.</u>				
Stainless Steel	1.8 lb/in				
Shelf Life:	1 year from ship date when stored in proper conditions 70° F and 50% relative humidity				



WALKER SUPPLY COMPANY
Graphics Equipment and Supplies