



# BANNER UPS® BY BUDNICK TTAPEDC

## TigerTape™ Premium Double Sided Banner Hem Tape

Banner Ups TigerTape™ is a 6.5 mil double coated polyester (PET) carrier film coated on both sides with a high deposition of a high tack acrylic pressure-sensitive adhesive (PSA). A high-performance banner hem tape specifically designed for the most demanding bonding applications, TigerTape™ provides a permanent bond on foams, plastics, metals, and composite materials subjected to a broad range of environmental conditions.

TigerTape™ is highly UV, temperature, and plasticizer resistant making it ideal for banner hemming applications. Materials should be stored at 70°F (21°C) with 50% relative humidity.

Backing/Carrier	PET - Polyester	Tensile		Min. Application Temp	50° F	
Adhesive	Acrylic	Elongation		Min. Service Temp	-40° F	
Thickness	6.5 Mils	Adhesion (liner)	170 oz/in	Max Short-Term Temp	275° F	
		Adhesion (unwind)	170 oz/in	Max Long-Term Temp	275° F	

### PRODUCT FEATURES

- High performance acrylic adhesive
- High conformability
- Plasticizer resistant
- High tack & peel
- High UV & temperature resistance
- Great outdoor performance

### MARKETS SERVED

- Signage, Banners, & Printing

### ADHESIVE TAPE APPLICATIONS

- Banner hemming applications
- General purpose bonding
- Trophy industry
- Coated paint surfaces

### ADHESIVE TAPE COLORS

- Translucent



**Data provided by Budnick Converting, Inc.**

The physical properties listed are typical values and are not to be considered as specifications. Our suggestions for use are based on tests we believe to be reliable. However, the purchaser must carry out their own tests to determine the suitability of the product for their internal use. Information is given in good faith, but without warranty.

It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry and free of grease and oil.

Shelf life from date of manufacture is based on the product being stored at 70°F(21°C) / 50% relative humidity out of direct sunlight.

Specification compliance is dynamic and should only be used as a general guide. Always confirm that the tape you are interested in currently complies with all specification requirements. Please verify that the product number that you select is available in the proper size and color to meet your specification.

