## Eagle Inkjet Media



## Optically Clear Mounting Film Permanent/Removable Adhesive

• Applications -- window, glass doors or any transparent surface when see-through graphics are needed for promotional advertising and point of purchase in retailers; eye-catching exhibit booths at trade shows.

## Construction

Product Number:	KJMOUNT/OPCPR/		
Carrier:	Optically Clear Polyester - 1 mil		
Adhesive:	Optically Clear Permanent & Removable Solvent Acrylic		
Liner:	One-Sided Silicone-Coated Polyester Film - 1.2 mil		
Product Scheme:	<ol> <li>Liner</li> <li>Adhesive</li> <li>Carrier</li> <li>Adhesive</li> <li>Liner</li> </ol>		Outside (Removable) Inside (Permanent)

**Typical Performance Values** 

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Outdoor Durability:	Up to 2 years;UV Ir	nhibitors added to adhesive	
Typical Adhesion Values:	180° Peel Test		
	<u>Substrate</u>	<u>24 hours</u>	
	Stainless Steel	Permanent 2.8 lb/in	
	Stainless Steel	Removable .6 lb/in	
Static Shear (1/2-inchx1/2-inchx500 grams)	> 24 hours		
Temperature:	50° F (Minimum for Substrate)		
Service Temperature Range:	-40° F to +180° F		
Chemical Resistance:	Resistant to detergent, gasoline, HCI - 10%, motor oil - SAE 20 and NH40H - 10%.		
Shelf Life:	1 year from ship date when stored in proper conditions 70° F and 50% relative humidity		

