



panoRama TwoWay Vision

A unique, clear PVC film embedded with a white prism technology.

Don't let your branding to get lost in the dark! The white prism technology transmits ambient light through the film for vibrant day-to-night window graphics.

Create stunning window graphics, viewed from both sides of the window, without the need for white ink.

APPLICATIONS

- Retail Store Fronts
- Corporate
 Environments
- Restaurants
- Flat and Slightly Curved Glass

panoRama TwoWay Vision

MATERIAL	
Face Film	Printable Clear (30%)/White (70%) Calendared PVC with Integrated White Prism
Back Side	Clear/White
Adhesive	Removable Clear Solvent Acrylic
Liner	Siliconized Paper – 7 mil (180µ +/-10µ)
Film Thickness	5 mil (120μ +/-10μ)
FR Certification	Not Tested

DURABILITY	
Interior	Up to 3 Years
Exterior	Up to 2 Years - Vertical Exposure under Normal Conditions
Environment	Humidity & Solvent Resistance – Very Good
Shelf Life	1 Year
Storage Requirements	Store at 59°F to 77°F (+15°C to +25°C) and Relative Humidity between 45% to 75%
Repositionable	Yes - During Initial Installation

APPLICATION/REMOVAL Application Temp +50°F to +86°F (+10°C to +30°C) Service Temp -14°F to +122°F (-25°C to +50°C) Removability Clean Removal with No Adhesive Residue, up to 6 Months - Adhesion May Increase over Time Removal Temp +50°F (+10°C) or Greater Exclusions NOT to Be Applied to Fresh Paint, Polycarbonate, and Some PVC (No Exhaustive List Available)

Surface must be clean and dry. Prevent contact with solvent or ammoniabased cleaners. For best results, clean glass or install surface with a mild detergent and water and dry thoroughly prior to application. ALWAYS clean and dry glass surface prior to application.

*For critical substrates and all surfaces, please test PRIOR to application.





Printing Methods

 Digital - Solvent, Eco-Solvent, UV, & Latex



Material Sizes

• 54" x 100'



Advantages

- Embedded White Prism Transmits Ambient Light for Vibrant Translucent Window Graphics Both Day and Night
- · No White Ink Needed
- Excellent Durability for Interior or Exterior Installations without Lamination
- Clean Removability (Up to 6 Months Without Residue)



For additional product information, performance, and warranty guidelines please contact Continental Grafix USA, Inc.

1-704-872-2216 · www.cgxusa.com

