



Hi-Stat® cling vinyl is a very soft, flexible vinyl which adheres to most clean, high polished smooth surfaces without adhesive.

Hi-Stat® White and Clear

8 mil. white or clear film laminated to a 8 or 10 pt. lay-flat board for ease of printing and die cutting.

Hi-Stat Opti-Cling® Optically Clear

8 mil. optically clear film laminated to a 5 mil. clear film liner for exceptional clarity.

Applications

- Window Advertising
- P.O.P. Window Decals
- Price Stickers
- Automotive Window Decals
- LED Screen Protection

Product Information

- Repositionable – printed decals can be reused if properly handled
- No solvents are needed for the application or removal
- Easy removal without leaving a trace of residue behind
- Can be wet applied
- For indoor and outdoor use

Print Compatibility

- Solvent
- Eco-Solvent
- Latex
- UV Wide Format

*It is not recommended to apply the top-coated (printed side) to glass, as the ink may transfer to the glass upon removal of the film.



TECHNICAL DATA ▶

Physical Properties		8 mil				
Color	White, Clear, and Optically Clear	White	Clear	White	Clear	Optically Clear
Finish	High Gloss	Board		Board		Clear Film
Film Material	Flexible Vinyl	8 pt		10 pt		5 mil
Surface Tension	32 Dynes Minimum	.62#		.67#		.60#
Min App Temp	+50° F / 10° C					
Service Temperature	-10° to +150° F / -23.3° to 60° C					
Chemical Resistance	Excellent					
Shelf Life	6 Months					
Indoor Durability	2 Years					
Outdoor Durability	3 Months					
Roll Size						
54" x 50 yd		•	•	•	•	•
60" x 50 yd		•	•	•	•	•

*Can be custom converted to meet your requirements including sheets.