

# Eagle Inkjet Media



## Adhesive Backed 3.5 mil Premium Gloss White Vinyl Permanent Adhesive for Solvent, Latex & UV Printers

- Can be used for interior and exterior signage
- Uses include outdoor signage, promotional and point of purchase graphics, trade show display
- Compatible with OEM Solvent, Latex & UV Curable Inks

### Construction

Product Number:	SOL/GWHTCAL/xxP
Adhesive:	Clear Permanent Acrylic
Film:	3.5 mil Vinyl
Liner:	88# Polycoated two sides
Finish:	Gloss White
Gloss Level:	70 (avg.) @ 60°

### Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Durability:	Outdoor -5 years unprinted				
Minimum Application Temperature:	+40° F (Minimum for Substrate)				
Service Temperature Range:	-40° F to +180° F				
Temperature Resistance:	-65° F to + 225° F				
Chemical Resistance:	Resistant to alkalis, mild acids, most petroleum based oil, grease and aliphatic solvent and salts.				
Typical Adhesion Values:	180° Peel Test <table><tr><td><u>Substrate</u></td><td><u>24 hrs.</u></td></tr><tr><td>Stainless Steel</td><td>3.0 lb/in</td></tr></table>	<u>Substrate</u>	<u>24 hrs.</u>	Stainless Steel	3.0 lb/in
<u>Substrate</u>	<u>24 hrs.</u>				
Stainless Steel	3.0 lb/in				
Shelf Life:	1 year from ship date when stored in proper conditions 70° F and 50% relative humidity				



**WALKER SUPPLY COMPANY**  
*Graphics Equipment and Supplies*

800-775-9528 • [www.walkersupply.com](http://www.walkersupply.com)