



Adhesive Backed 3 mil Gloss White Vinyl Permanent Gray Adhesive & Air Release Liner for Solvent, Latex & UV Printers

- Can be used for interior and exterior signage
- Uses include outdoor signage, promotional and point of purchase graphics, trade show displays
- The textured liner has embossed pattern that produces channels in the adhesive that will help air to escape during application.
- Compatible with OEM Solvent, Latex & UV Curable Inks

Construction

| | |
|-----------------|--------------------------|
| Product Number: | SOL/WHTCAL/xxAR |
| Adhesive: | Permanent Gray Acrylic |
| Film: | 3 mil Vinyl |
| Liner: | Air Release 90# Lay Flat |
| Finish: | Gloss Clear |
| Gloss Level: | 80 (avg.) @ 60° |

Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

| | | |
|----------------------------------|--|----------------|
| Printing: | Outdoor -5 years unprinted | |
| Minimum Application Temperature: | +50° F (Minimum for Substrate) | |
| Service Temperature Range: | -40° F to +180° F | |
| Chemical Resistance: | Resistant to alkalis, mild acids, most petroleum based oil, grease and aliphatic solvents and salts. | |
| Typical Adhesion Values: | 180° Peel Test | |
| | <u>Substrate</u> | <u>24 hrs.</u> |
| | Stainless Steel | 3.0 lb/in |
| Shelf Life: | 1 year from ship date when stored in proper conditions 70° F and 50% relative humidity | |