

Adhesive Backed 3 mil Luster Vinyl Laminate

- UV protection added to vinyl
- Suitable for indoor and outdoor applications

Construction

Product Number:	KJLLAM
Adhesive:	Clear Permanent Acrylic
Film:	3 mil PVC (with UV absorber)
Liner:	4.6 mil (78# C1S Liner)
Gloss Level:	35-45 (avg.) @ 60°

Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Durability:	Outdoor - up to 3 years	
Minimum Application Temperature:	+ 40° F (Minimum for Substrate)	
Service Temperature Range:	-40° F to +180° F (-46° C to + 82° C)	
Temperature Resistance:	-65° F to + 225° F	
Chemical Resistance:	Resistant to alkalis, mild acids, most petroleum based oil, grease and aliphatic solvent and salts.	
Typical Adhesion Values:	180° Peel Test	
	<u>Substrate</u>	<u>24 hrs.</u>
	Stainless Steel	3.0 lb/in
Shelf Life:	2 years from manufactured date when stored in proper conditions 70° F and 50% relative humidity	

**WALKER SUPPLY COMPANY***Graphics Equipment and Supplies*301-738-6500 / www.walkersupply.com