



# Adhesive Backed 3.2 mil Translucent White Vinyl Permanent Adhesive for Solvent, Latex & UV Printers

- Used for interior and exterior lighted signage
- Backlit graphics, point of purchase, trade show displays and window graphics
- Compatible with OEM Solvent, Latex & UV Curable Inks

## Construction

Product Number:	SOL/CALTRANS - wound print side out
Adhesive:	Clear Permanent Acrylic
Film:	3.2 mil White Translucent Vinyl
Liner:	88 lb Polycoated two sides
Finish:	White Translucent
Opacity:	78%
Gloss Level:	25 (avg.) @ 60°

## Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Durability:	Outdoor - 5 years unprinted
Minimum Application Temperature:	+40° F (Minimum for Substrate)
Service Temperature Range:	-40° F to +180° F
Temperature Resistance:	-65° F to + 225° F
Chemical Resistance:	Resistant to alkalis, mild acids, most petroleum based oil, grease and aliphatic solvent and salts.
Typical Adhesion Values:	180° Peel Test <u>Substrate</u> <u>24 hours</u> Stainless Steel                3.0 lb/in
Shelf Life:	1 year from ship date when stored in proper conditions 70° F and 50% relative humidity