

## Adhesive Backed 3.5 mil Satin White Vinyl High Tack Permanent Adhesive for Solvent, Latex & UV Printers

- Aggressive permanent adhesive is designed for hard to stick and low energy surfaces
- Can be used for interior and exterior signage
- Uses include excellent adhesion to plastic & textured surfaces and in cold temperature environments
- Compatible with OEM Latex, Solvent and Mild Solvent Inks

## Construction

Product Number:	SOL/375WHTCAL/xxHTP
Adhesive:	Clear Permanent High Tack Acrylic
Film:	3.5 mil Vinyl
Liner:	90# Lay Flat Liner - Polycoated two sides
Finish:	Satin White
Gloss Level:	30 (avg) @ 60°

## **Typical Performance Values**

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Printing:	Outdoor - 5 years unprinted
Minimum Application Temperature:	30°F (Minimum for Substrate)
Service Temperature Range:	-65° F to 225° F
Chemical Resistance:	Resistant to alkalies, mild acids, most petroleum based oil, grease and aliphatic solvent and salts.
Typical Adhesion Values:	180° Peel Test <u>Substrate</u> <u>15 min.</u> Stainless Steel 5.0 lb/in
Shelf Life:	1 year from ship date when stored in proper conditions 70° F and 50% relative humidity

