

# CE7000 SERIES

# GRAPHTEC BLADES

	<b>CB09UB</b>	<b>Angle: 45° Diameter 0.9mm</b>	Standard blade for vinyl cutting & self-adhesive marking film (PVC film) up to 0.25 mm thick. Maximum cutting distance is approx. 13,123 ft.
	<b>CB09UB-K60</b>	<b>Angle: 30° Diameter 0.9mm</b>	Supersteel Blade for cutting the window tint film or thin film, up to 0.25 mm thick.
	<b>CB15U</b>	<b>Angle: 45° Diameter 1.5mm</b>	Supersteel blade for cutting rigid or thicker media, 0.25 mm to 0.5 mm thick. (laminates, smart device, device screen protection media)
	<b>CB15U-K30</b>	<b>Angle: 60° Diameter 1.5mm</b>	Supersteel Blade for cutting rigid media, 0.25 mm to 0.5 mm thick. And also small detailed characters on marking film (up to 0.25mm). Recommended blade for sandblast rubber resist media cutting and Avery Series of Reflective sheeting.
	<b>CB15UA</b>	<b>Angle: 45° Diameter 1.5mm</b>	Supersteel Blade for cutting high-intensity reflective film or harder film.
	<b>CB15UA-K30</b>	<b>Angle: 60° Diameter 1.5mm</b>	Supersteel Blade for cutting rigid media, 0.25 mm to 0.5 mm thick. And also small detailed characters on marking film (up to 0.25mm). Recommended blade for sandblast rubber resist media cutting and Avery Series of Reflective sheeting.

Please Refer To The Users Manual For Blade/Application Compatibility.

# CE7000 SERIES

# GRAPHTEC BLADE HOLDERS

	<b>PHP31 FIBERSTEADTLER</b>	<b>FIBERSTEADTLER</b> Lumocolor Fiber Tip Pen Holder.
	<b>PHP33-CB09N-HS SPRING BUILT-IN</b>	Compatible with Blades: <b>CB09UA • CB09UA-K60 • CB09UB • CB09UB-K60</b> 0.9mm, blue top, black ABS tip. Not recommended for CB09UA blades with springs.
	<b>PHP33-CB15N-HS SPRING BUILT-IN</b>	Compatible with Blades: <b>CB15U • CB15U-K30* • CB15UA • CB15U-K20-2SP • CB15UA-K30 • CB15UB</b> 1.5mm**, red top, black ABS tip.
	<b>PHP34-BALL</b>	Ballpoint pen holder for black, oil based pen (KB700-BK).
	<b>PHP35-CB09-HS SPRING BUILT-IN</b>	Compatible with Blades: <b>CB09UA • CB09UA-K60 • CB09UB • CB09UB-K60</b> 0.9mm, blue top, black brass tip. <b>ATTENTION:</b> If you are using CB09UA Blade (with spring); Insert only the CB09UA blade without the spring. This blade-holder, plunger design already includes an internal spring. These brass tip blade-holders, plungers are more rigid and lend to more accurate cutting.
	<b>PHP35-CB15-HS SPRING BUILT-IN</b>	Compatible with Blades: <b>CB15U • CB15U-K30* • CB15UA • CB15U-K20-2SP • CB15UA-K30 • CB15UB</b> 1.5mm**, red top, black brass tip. These brass tip blade-holders/plungers are more rigid & lend to more accurate cutting. <b>NOTE:</b> REMOVE CB15 SP Blade spring before installing into this Blade-holder. DO NOT install any blade spring to more accurate cuts.

\* Suitable for a rigid media, 0.25 mm to 0.5 mm thick or cutting small detailed characters on marking film (up to 0.25mm).

\*\* Require to remove spring.

Recommended Setting On Control Panel: OTHER\* Offset +31, Force 10-14, Speed 30 or less, Acceleration 2

CE7000-40, 60 and 130 Plus only. \*CB15U-K30 can not be selected as the tool type. Please select (OTHER) instead.