



## Adhesive Backed 3 mil Gloss White Vinyl Removable Gray Adhesive & Air Release Liner for Solvent, Latex & UV Printers

- Designed for interior floor graphic applications on smooth indoor floor surfaces - such as sealed concrete, commercial PVC and ceramic tile - use with slip-resistant floor laminate
- Excellent for use in medium-term vehicle graphics - side panels
- Air release liner assists in reduced wrinkling and air bubbles
- Compatible with OEM Solvent, Latex & UV Curable Inks

### Construction

Product Number:	SOL/WHTCALAR/xxR
Adhesive:	Gray Removable Acrylic
Film:	3 mil Calendered Vinyl
Liner:	90# Lay Flat
Finish:	Gloss White
Gloss Level:	85 (avg.) @ 60°

### Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Durability:	Outdoor -5 years unprinted Removable - up to 1 year
Minimum Application Temperature:	+50° F (Minimum for Substrate)
Service Temperature Range:	-40° F to +180° F
Chemical Resistance:	Resistant to alkalies, mild acids, most petroleum based oil, grease and aliphatic solvents and salts.
Typical Adhesion Values:	180° Peel Test Substrate                      24 hrs. Stainless Steel              2.0 lb/in
Shelf Life:	1 year from ship date when stored in proper conditions 70° F and 50% relative humidity



**WALKER SUPPLY COMPANY**  
Graphics Equipment and Supplies