## **Eagle Inkjet Media**



- Great when glare is not needed
- Can be used for interior and exterior signage
- Uses include outdoor signage, promotional and point of purchase graphics, trade show displays
- Compatible with OEM Latex, Solvent and Mild Solvent Inks

## Construction

Product Number:	SOL/6GWHTCAL/xxP
Adhesive:	Clear Permanent Acrylic
Film:	6 mil Vinyl
Liner:	88 lb Polycoated two sides
Finish:	Matte White
Gloss Level:	90 (avg.) @ 60°

## **Typical Performance Values**

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Printing:	Outdoor - 3 years unprinted
Minimum Application Temperature:	+ 50° F (Minimum for Substrate)
Service Temperature Range:	-40° F to + 180° F (-46° C to + 82° C)
Chemical Resistance:	Resistant to alkalies, mild acids, most petroleum based oil, grease and aliphatic solvents and salts.
Typical Adhesion Values:	180° Peel Test <u>Substrate</u> <u>24 hrs.</u> Stainless Steel 3.0 lb/in
Shelf Life:	1 year from ship date when stored in proper conditions 70° F and 50% relative humidity

page 1/2

