

Details

- Dot adhesive technology, Permanent adhesive, Matte surface PVC Calender.
- Designed to remove bubbles with high performance without using special liquid mixture.
- Repositioning available initially, but the adhesive be stronger after positioned.
- Can be installed by anyone without special techniques because of the dot technology.
- Water based Pigment ink, UV, Latex ink compatibility

* Condition / Setting

Highly recommend to test this sample roll before you try to target

Recommended for indoor usage

Clean the mounting object before applying this film



Specifications

Standard length (m)	30m	Width (inch)	42", 60"
Total weight (g/ m²)	265g/ m² (±10%)	Coating	Resin
Base weight (g/ m²)	115g/ m² (±10%)	Base Material	PVC
Total caliper (μ)	235μ (±10%)	Printer	E S Uv L
Base caliper (μ)	100μ (±10%)	Peel Strength (SUS, gf/25mm)	Initial 20 min. ≥ 100
Surface	Matte		3 days ≥ 450
Inner Core (inch)	3		

KEY FEATURES

- Dot adhesive technology
- Permanent adhesive
- White matte finish
- Easy to install
- Bubbles free

Application

- Architectural window decorations, Glass and Plastic flatness, Window graphics, Trade Show

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional
- Storage : Recommended to store in closed original packing in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.
(Humidity 35 ~ 65% RH)
- Shelf Life : One year stored in original packaging at recommended temperature

* Cautions

- Recommended to put the blank space when printing the products
- For outdoor use, recommended to use outdoor lamination film to prevent decoloration.
- Recommended to use the products after complete or enough drying time
- Recommended to use double-sided tape or proper finish to prevent detachment from the substrate.