



Adhesive Backed 3 mil Gloss Clear Vinyl Permanent Adhesive for Solvent Printers

- Can be used for interior and exterior signage
- Uses include outdoor signage, promotional and point of purchase graphics, trade show displays
- Compatible with OEM Solvent Inks

Construction

Product Number:	SOL/CLEARCAL
Adhesive:	Clear Permanent Acrylic
Film:	3 mil Vinyl
Liner:	88 lb Lay Flat
Finish:	Gloss Clear
Gloss Level:	80 (avg.) @ 60°

Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Printing:	Outdoor - 5 years unprinted
Minimum Application Temperature:	+40° F (Minimum for Substrate)
Service Temperature Range:	-40° F to +180° F
Temperature Resistance:	-65° F to + 225°
Chemical Resistance:	Resistant to alkalies, mild acids, most petroleum based oil, grease and aliphatic solvents and salts.
Typical Adhesion Values:	180° Peel Test Substrate 24 hrs. Stainless Steel 3.0 lb/in
Shelf Life:	1 year from ship date when stored in proper conditions 70° F and 50% relative humidity