# Safety Data Sheet

Manufactured For:

# Press Smart Silli Slip

SDS Number: Silli Slip

Revision Date: 08/02/2015

Page 1 of 5

# PRODUCT AND COMPANY IDENTIFICATION

## Manufacturer

Manufactured For: Press Smart Products 13405 Mill Bank Road Plainfield, Illinois 60544

Contact: Phone: Safety Department 630-363-8820

2	HAZARDS IDENTIFICATION
Route of Entry:	Inhalation; Skin;
Inhalation:	Excessive inhalation may cause headaches, dizziness and nausea.
Skin Contact:	May cause irritation. Prolonged skin contact may cause defatting and dermatitis.
Eye Contact:	May cause irritation and conjunctivitis.
Ingestion:	Do not induce vomiting. Consult Mmedical attantion.

GHS Signal Word: DANGER

GHS Hazard Pictograms:



GHS Classifications:

- Health, Aspiration hazard, 1
- Health, Serious Eye Damage/Eye Irritation, 2 B
- Health, Specific target organ toxicity Repeated exposure, 2
- Health, Skin corrosion/irritation, 3
- Physical, Flammable Liquids, 4

GHS Phrases:

- H304 May be fatal if swallowed and enters airways
- H320 Causes eye irritation
- H373 May cause damage to organs through prolonged or repeated exposure
- H316 Causes mild skin irritation
- H227 Combustible liquid

GHS Precautionary Statements:

P101 - If medical advice is needed, have product container or label at hand.

- P102 Keep out of reach of children.
- P103 Read label before use.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do.

# Safety Data Sheet Manufactured For:

# Press Smart Silli Slip

#### SDS Number: Silli Slip

Revision Date: 08/02/2015 Page 2 of 5

Continue rinsing. Seek medical attention.

P404 - Store in a closed container.

P240 - Ground/bond container and receiving equipment.

P243 - Take precautionary measures against static discharge.

P264 - Wash \_ thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

#### **COMPOSITION/INFORMATION ON INGREDIENTS**

#### Ingredients:

Cas #   Percentage	Chemical Name
63148-62-9	Siloxanes and Silicones, di-Me
64742-47-8	Distillates, petroleum, hydrotreated light

4	FIRST AID MEASURES
Inhalation:	If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention. Give oxygen or artificail respiration if needed.
Skin Contact:	Remove contaminated clothing. Wash skin with soap and water Give medical attention. Wash clothing seperately and clean shoes before reuse.
Eye Contact:	Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Remove contact lenses if worn.
Ingestion:	Do not induce vomiting. Seek prompt, qualified medical attention.

#### FIRE FIGHTING MEASURES

Flash Point: Flash Point Method:	110°F T.C.C.
Burning Rate:	Unknown
LEL:	1.0
UEL:	6.0

Extinguisning Media: Foam, CO2, Water fog, Dry Chemical

## ACCIDENTAL RELEASE MEASURES

Eliminate Ignition sources and contain spill. Pick up excess with inert absorbant material and place into separate waste container.

Keep away from drains and ground water.

Watch out for slippery conditions when spillage.

Wear self contained breathing apparatus, rubber boots and heavy rubber gloves.

#### Waste Disposal Method

Empty aerosol cans should not be punctured or incinerated; Dispose of in accordance with local, state and federal regulations.

# Safety Data Sheet Manufactured For:

# **Press Smart Silli Slip**

Revision Date: 08/02/2015

Page 3 of 5

# HANDLING AND STORAGE Handling Precautions: Keep material out of reach of children. Handle with care and avoid spillage on the floor (slippage). Keep away from sources of ignition. Do not puncture or drop containers. Consider normal working hygiene. Keep away from sources of ignition. **Storage Requirements:** Suitable packing materials. **EXPOSURE CONTROLS/PERSONAL PROTECTION**

Engineering Controls:	All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).		
Personal Protective Equip:	Use local exhaust at filling zones and where leakage is probable. Use mechanical (general) ventilation for storage areas. HMIS PP, C   Safety Glasses, Gloves, Apron		

# PHYSICAL AND CHEMICAL PROPERTIES

**Appearance: Physical State:** Particle Size: Spec Grav./Density: Viscosity:

SDS Number: Silli Slip

Colorless liquid. Liquid DNA 9.09 lbs. per gallon Slightly viscus

Odor: Solubility: Softening Point: Percent Volatile:

Slight citrus to pine scent Insoluble in water DNA 70%

# **STABILITY AND REACTIVITY**

Stability:	Product is stable under normal conditions.
Conditions to Avoid:	Heat, sparks and open flames
Materials to Avoid:	Strong Oxidizing Agents.
Hazardous Decomposition:	Carbon Monoxide, Oxides of Silicone, Nitric and sulfuric Acids, Carbon Dioxide.
Hazardous Polymerization:	Will not occur.

# Safety Data Sheet

Manufactured For:

# Press Smart Silli Slip

SDS Number: Silli Slip

Revision Date: 08/02/2015

Page 4 of 5

# **TOXICOLOGICAL INFORMATION**

Informatin on Toxicological Effects:

Effects of Overexposure - Inhalation: Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness and stupor (CNS Depression)

**Effects of Overexposure - Skin Contact:** Contact with skin may cause mild irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermititis (rash). Personnel with pre-existing skin disorders should avoid contact with this product.

Effects of overexposure - Eye Contact: May cause eye irritaion and conjunctivitis.

**Effects of Overexposure - Ingestion:** This material may be harmful or fatal if swalklowed. Harmful or fatal if liquid is aspirated into lungs. Irritating to mouth, throat and stomach. can be redily absorbed by the stomach and intestnal tract. Symptoms include burning sensation of the mouth and esophagus, nausea, vomitting, diarrhea, dizziness staggering gait, drowsiness, loss of consciousness and delerium as well as additional central nervous system effects.

**Effects of Overexposure - Chronic Hazards:** Possible brain damage from overexposure. Overexposure may cause nervous system damage. Chronic effests of ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunctiion. Significatnt exposure to the chemical may adversly affect people with chronic disease of the respiratory system, central nervous system, kidney, liver, skin and/or eyes.

Accute toxicity values of this product have not been tested. Data on individual components are listed below:

CAS-No	Name according to EEC	<u>Oral LD50, mg/kg</u>	Dermal LD50, mg/kg	<u>Vapor LC50, mg/L</u>
64742-47-8	3 Aliphatic hydrocarbon	>5,000	>2,000	>20.0

12

# **ECOLOGICAL INFORMATION**

No Information is available

# DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state and federal regulations.

# 14 TRANSPORT INFORMATION

UN #: UN 1268, Class: 3, Proper Shipping Name: Petroleum distillates, n.o.s. or petroleum products, n.o.s.

# Safety Data Sheet Manufactured For:

# **Press Smart Silli Slip**

Revision Date: 08/02/2015

Page 5 of 5

SDS Number: Silli Slip

# **REGULATORY INFORMATION**

COMPONENT / (CAS/PERC) / CODES

\*Mineral Spirits (64742489 n/a%) TSCA

REGULATORY KEY DESCRIPTIONS

TSCA = Toxic Substances Control Act

**OTHER INFORMATION** 

## **Disclaimer:**

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).