

ALM3222

AUTOMATIC LAMINATOR



With the Dry-Lam Automatic Laminating Machines (ALMs), quality laminating is simple, requires very little space, and is more affordable than you might think. Just push a button and your ALM3222 automatically feeds, laminates, cuts, and trims digitally printed materials in one pass.

- ▶ Ultra-quick warm-up time of 5 minutes
- ▶ Automatic single or double-sided lamination
- ▶ Adjustable for automatically flush cut or sealed edge trim options; micro-adjustable for precise flush cut or custom encapsulation
- ▶ Custom Extended Warranties: Choose the extra coverage that's right for you!



Width: 13"

Model	ALM3222
Laminating Width	13"
Speed	20 - 68" per minute
Film Thickness	1.5 - 10 mil (10 mil border cut only)
Laminating Thickness	20 lb bond - 100 lb cover
Heat Type	Heated Rollers: Dual heat
Temperature Range	170 - 270 °F
Warm-up Time	5 minutes
Paper Sizes	8.5" x 11," 11" x 17," 12" x 18," and 13" x 19"
Paper Feed Capacity	200 Sheets, Adjustable Paper Guide
Trimming Methods	Flush Cut or Border Cut
Operation Panel	LCD Display
Power Supply	1200W, 120 VAC, 60 Hz, 10A
Weight	Laminator: 97 lbs, Optional Stand: 52.9 lbs.

Recommended Film

- ▶ SAP75: 3 mil Gloss
- ▶ SAP125: 5.0 mil Gloss
- ▶ ECO125: 5.0 mil Silk Matte