

CAD-CUT® Thermo-GRIP® Heat Transfer Vinyl

Application Instructions

1 1-Color Application Instructions

- Time:** 6-8 seconds
- Temperature:** 330°F/165°C
- Pressure:** Medium
- Peel:** Warm

2 2-Color Application Instructions

- Background:** Apply for 2 seconds, peel hot
- Foreground:** Apply for 2 seconds, peel hot
- Final Application:** Cover with Kraft paper and apply for 10 seconds
- Temperature:** 330°F/165°C
- Pressure:** Medium

Care Instructions

Machine wash inside-out using mild detergent. Do not use bleach. Dry at a normal dryer setting on household machines. Do not dry clean.

Storage

Store in a cool and dry area around 65 to 70 degrees Fahrenheit with 50% relative humidity. Keep away from direct heat, sunlight and humidity. Recommended shelf life is one year.

Material/Fabric Compatibility

- 100% Cotton
- 100% Polyester
- 100% Preshrunk Cotton
- Cotton/Poly Blends
- Nylon

Material Combination Instructions

Foreground material:

Select One

Background material:

Select One

Cutter Guidelines

Cutter	Blade	Force	Offset	Speed
GCC	45°/60°	140-170g/120-170g	.25 / .50	15-50 cm/s
Graphtec	45°	18-20	0	30cm/s
Ioline 100	45°	275-300g	.15	12:30
Ioline 300	30°	180g	.15	12:15
Roland GS-24	45°	140-160g	.25	30cm/s

Note: Always test cut prior to any production run. For optimal cutting and weeding, maintain a line thickness of at least 1/16" for lettering & logos.