

# CAD-CUT® Hologram Heat Transfer Vinyl

## Application Instructions

### 1-Color Application Instructions

- Time:** 10 - 15 seconds
- Temperature:** 320°F/160°C
- Pressure:** Firm
- Peel:** Cold

### Hotronix® 360 IQ™ Hat Press

- Time:** 45 seconds
- Upper:** 280°F
- Lower:** 320°F
- Pressure:** Medium
- Peel:** Warm/Cold
- Cover Sheet:** 1/8" Foam Pad

### Care Instructions

Machine wash inside-out using mild detergent. Do not use bleach. Dry at a normal dryer setting on household machines. Do not dry clean.

### Storage

Store in a cool and dry area around 65 to 70 degrees Fahrenheit with 50% relative humidity. Keep away from direct heat, sunlight and humidity. Recommended shelf life is one year.

### Material/Fabric Compatibility

- 100% Cotton
- 100% Polyester
- 100% Preshrunk Cotton
- Cotton/Poly Blends

### Material Combination Instructions

Foreground material:

Select One

▼

Background material:

Select One

▼

### Cutter Guidelines

Cutter	Blade	Force	Offset	Speed
GCC	45°/60°	90-150g/90-130g	.25 / .50	20 - 25 cm/s
Graphtec	45°	15-17	0	30cm/s
Roland GS-24	45°	140-160g	.25	30cm/s

**Note:** Always test cut prior to any production run. For optimal cutting and weeding, maintain a line thickness of at least 1/16" for lettering & logos.

[View Craft Cutter Settings](#)