

CAD-CUT® Chroma Bling Heat Transfer Vinyl

Application Instructions

1-Color Application Instructions

| | |
|---------------------|-----------------|
| Time: | 10 seconds |
| Temperature: | 300°F/150°C |
| Pressure: | Medium (45 psi) |
| Peel: | Cold |

Care Instructions

Machine wash warm.
Do not use bleach. Tumble dry, low heat on household machines. Cool iron, no steam. Do not dry clean.

Storage

Store in a cool and dry area around 65 to 70 degrees Fahrenheit with 50% relative humidity. Keep away from direct heat, sunlight and humidity. Recommended shelf life is one year.

Material/Fabric Compatibility

100% Cotton
100% Polyester
Cotton/Poly Blends

Material Combination Instructions

| | |
|---|---|
| Foreground material: | Background material: |
| <input type="text" value="Select One"/> | <input type="text" value="Select One"/> |

Cutter Guidelines

| Cutter | Blade | Force | Offset | Speed |
|--------------|-------|----------|--------|-----------|
| Roland GS-24 | 45° | 120-150g | .25 | 25-30cm/s |
| Graphtec | 45° | 10-16 | 0 | 25-30cm/s |

Note: Always test cut prior to any production run. For optimal cutting and weeding, maintain a line thickness of at least 1/16" for lettering & logos.

 [View Craft Cutter Settings](#)
